


Foilbond™ TC

HIGH PERFORMANCE, UV CURABLE THRU CURE
ADHESIVE OPTIMIZED FOR COLD FOILING APPLICATION



Foilbond™ TC

permits cold foiling on a wide variety of substrates and eliminates the need for costly, heated rotary dies. The technology uses the respective print process in combination with the printing plates to transfer the desired image to the substrate with final UV curing of the adhesive.

Applicable substrates include:

- Polyethylene (PE) and Polypropylene (PP)
- Vinyl
- Various paper substrates; coated semi-gloss or gloss material
- Plastic laminate tubes
- Unsupported and heat sensitive films
- Cartonboard

Applications include any that require foiling or the appearance of foil, such as cosmetics, wine labelling, packaging etc. Foilbond™ TC can be used in combination with most of Flint Group Narrow Web ink technologies.

PROPERTIES	BENEFITS
<ul style="list-style-type: none">• Excellent bonding	<ul style="list-style-type: none">• Fine detail foiling
<ul style="list-style-type: none">• Press ready	<ul style="list-style-type: none">• Easy to use
<ul style="list-style-type: none">• Single component formulation	<ul style="list-style-type: none">• Reduced make-ready
<ul style="list-style-type: none">• Colored adhesive	<ul style="list-style-type: none">• Easy to see adhesive is easy to work with

Foilbond™ TC

Availability

- in UV Flexo UVH00003
- in UV Letterpress UVH00004
- in UV Screen UVH00005

The information contained in this brief product presentation is based on long experience of Flint Group Narrow Web and on internal standardised tests. It is not to be interpreted as a warranty or guarantee in any form as conditions beyond our control can affect the quality of the printing. If there is any doubt, the user should always make every effort to ensure that the products used are appropriate for the purpose.

FOILBOND™ TC OFFERS:

- Excellent cold foil lamination adhesion
- Proven suitability on a wide variety of substrates
- Capability of being used with many ink technologies, very suitable for combination printing
- High curing speed
- Allows for higher printing speeds relative to hot foil stamping

Cold Foiling Technology:

Foilbond™ TC is a UV curable adhesive developed for a wide variety of substrates and optimized for thru cure cold foiling technology. The technology involves the printing of Foilbond™ TC ThruCure adhesive onto the desired substrate using for example the flexographic printing technique. The substrate, along with the Foilbond™ TC adhesive, is nipped with the foil and passed through the UV unit while still under pressure. The foil transfers from its carrier and adheres to the adhesive. This technique eliminates the need for costly, heated rotary engraved dies, or changes in press configuration. With a wider range of running speeds compared to those of traditional hot foil stamping, the converter is offered a number of major benefits. These include halftone metallic effects, and clear fine detail foiling with no recession of the foiled image into the substrate. This technology is extremely useful in combination print applications; the process is in-line, therefore allowing the printer to print various inks on top of or underneath the foiling without having to reconfigure the press.

**For more details on Foilbond™ TC,
call your nearest Flint Group Narrow Web office or dealer.**

Flint Group Narrow Web
15500 28th Avenue North,
Plymouth, MN 55447, USA
www.flintgrp.com

T +1 763 559 5911
Toll Free in the U.S.(800) 328 7838
F +1 763 559 0243
info.narrowweb@flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability. For application details refer to Technical Data Sheet.

Product names followed by ® are trademarks registered by Flint Group Incorporated.