

# Hydrokett™ ZEN

A HIGH PERFORMANCE PRESS STABLE, WATER-BASED FLEXO INK FOR SELF ADHESIVE LABELS



## Hydrokett™ ZEN Ink System

can be used in all flexographic print units provided the ink is dried with hot air or IR dryers in combination with air stream blowing on web. Hydrokett™ ZEN can be used with negative doctor blade as well as in a chambered doctor blade system.

## Suitable for a wide variety of applications

- Self adhesive labels (coated & uncoated papers, and many films)
- Cartons (carton boards)
- Tags
- In mold labels

Can be hot foil blocked and thermal transfer overprinted.

PROPERTIES	BENEFITS
• Excellent press stability and very low maintenance	• Consistent high print quality; Improved profitability due to reduced waste and press down time
• Good adhesion on many substrates	• Robust ink, lower inventory
• Superior printability, great dot sharpness	• Best print quality obtainable with water-based flexo; higher quality labels
• Outstanding colour strength and excellent mileage	• Improved print result and higher value
• High printing speed	• Improved productivity
• User-friendly raw materials	• Environmentally friendly
• Easy clean up	• Faster press change overs, higher productivity

# Hydrokett™ ZEN

## Availability

- Full range of Pantone® basic colours
- 4 colour process set
- Opaque white

The information contained in this brief product presentation is based on long experience of Flint Group Narrow Web and on internal standardised tests. It is not to be interpreted as a warranty or guarantee in any form as conditions beyond our control can affect the quality of the printing. If there is any doubt, the user should always make every effort to ensure that the products used are appropriate for the purpose.

- very suitable
- suitable
- usable
- not suitable

## HYDROKETT™ ZEN OFFERS:

- Excellent press stability
- Superior printability and dot reproduction
- Outstanding colour strength
- Excellent for high definition process printing
- Low viscosity, low foaming
- Easy maintenance and clean up
- One ink system to print on a wide variety of substrates

HYDROKETT™ ZEN	
<b>Printing Speed</b>	200 - 500 ft/min
<b>Anilox Volume*</b>	
<b>Line &amp; Solids Printing</b>	2 - 5 BCM
<b>Process Printing for Strong System</b>	1 - 2 BCM
<b>Printability</b>	
Process	•••
Solids	•••
<b>Press Stability</b>	
	•••
<b>Material Suitability</b>	
Paper	•••
TC thermal papers	•
TC filmic substrates	•••
Filmic substrates	••
<b>Resistance Properties</b>	
Chemical	-
Water	••
Solvent	-
<b>Combination Printing</b>	
UV Flexo	••
UV Letterpress	••
Water-based flexo	•••
UV Flexo varnish	•••
UV Screen	•
<b>Variable Info Printing</b>	
Thermal overprinting	-
Thermal transfer	•••
Hot foil	••
Cold foil	•••
Laser overprinting	••
Ink jet overprinting	••
<b>Lamination with</b>	
Radical adhesive	••
Cationic adhesive	-

\*Anilox volume is expressed in theoretical volume of anilox roller to obtain process density or to match Pantone® shades.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH)