CombiWhite EkoCure®ANCORA™

A FOOD CONTACT MATERIAL APPLICATION COMPLIANT OVERPRINTABLE OPAQUE WHITE SCREEN INK WITH EXCELLENT OVERPRINT PERFORMANCE WITH ALL PRINT METHODS



CombiWhite EkoCure[®] ANCORA[™]

- Is suitable for specific demands in food labels applications
- Optimized for combination printing with Ekocure[®] ANCORA[™] inks
- Can be used in all rotary screen units (SCREENY and STORK) and fast running flatbed presses, provided the inks is cured (exposed to UV LED light)

Suitable for a wide variety of applications

Self-adhesive labels

(PE, PP, top coated PE & PP)

PROPERTIES	BENEFITS
Very high opacity opaque white	Less ink required to obtain same opacity
Excellent overprintability	 Improved brand image and productivity
Very Low migration	 Possibility to use UV Flexo in various food packaging and label applications where specific low migration is required.
 Complies with Nestlé Guidance note for Packaging inks and with the Swiss Ordinance list 	 Meet stringent demands of food packaging applications
Press ready for any combination	Faster production, less make ready, less waste
 Great print sharpness, both in text and solids 	Best print quality obtainable with UV screen white

CombiWhite EkoCure[®] ANCORA[™]

Availability

• Only available as opaque white shade.

EkoCure® LED Technology Delivers Economical and Sustainable Benefits

CombiWhite EkoCure® ANCORA™ is developed using specially selected raw materials that match the narrow and targeted wavelenght area that is typical for UV LED lamp output.

THE FACTS	THE BENEFITS
UV LED lamps require significantly less energy	• Estimated 40% reduction of energy costs & lower operating costs
 Large ventilation systems are eliminated and the UV LED curing unit & power supply are smaller and more compact 	 Manufacturing space is reduced and energy is saved
UV LED lamps produce less heat	 Lower heat emission - lights do not need to warm up or cool down; offers ability to run heat sensitive films on a press with little heat management
UV LED lamps are ozone and mercury free	 Safe working conditions and improved air quality
 UV LED lamps have approximately a 20,000 hour life, compared to 2,000 hour life of a standard bulb 	 Printers can save time and money not replacing standard mercury vapor bulbs
UV LED offers consistent UV output	 LED does not degradate quickly like mercury lamps - affecting cure speed and productivity and assuredness of quality!
UV LED lamps are very low maintenance	 No need to clean reflectors and no bulb replacement - increasing press UPTIME

CombiWhite EkoCure® ANCORA™ delivers reliable quality suitable for stringent food and packaging applications:

- Formulated in accordance with EuPIA Exclusion Criteria
- Formulated in such a way as to minimize both potential migration through the substrate and set off from the printed outer side to the food contact surgace in the stack or the reel.
- Packaging inks are manufactured in accordance with EuPIA Good Manufacturing Practices.

The ultimate verification of compliance can only be done on the finishes printed and/or varnished food package. The manufacturer of the final article has the legal responsibility to ensure that it is fit for the intended purpose as food packaging. Data on migration should always be obtained by a practical migration test, done by the converter and the packer/filler, of the individual printed packaging material and article in its finished state, taking into account normal and foreseeable conditions of use. Provided that the packaging inks are correctly processed and that the food packaging is designed in a way that there is no direct food contact with the print, this will allow compliance of the final product with existing legal provisions.

For more details on CombiWhite EkoCure[®] ANCORA[™], call your nearest Flint Group Narrow Web office or dealer.

Flint Group Narrow Web

19401, Rogers Drive, Suite 200 Rogers, MN 55374, USA www.flintgrp.com info.narrowweb@flintgrp.com The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Product names followed by (are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH)