

NEWSMAN

Rely on us.SM

The Ink Newspaper Professionals Choose

683 BLACK

PRODUCT CODE	11005624
DESCRIPTION	Newsman 683 black was developed specifically for use in presses with overshot ducting systems. Newsman 683 black is based on a "single phase" vehicle system that has been designed for fast penetration of news print stocks. It has robust lithographic properties and displays excellent rub resistance across a wide variety of standard newsprint and specialty grade newsprint stocks.
FEATURES	<ul style="list-style-type: none">*Fast paper penetration*High pigmentation (carbon) levels*Excellent rub resistance*Low mist levels*Robust lithographic qualities*Available in pumpable grade only
PACKAGING	20 Tonne Iso-tainer & 1200kg tote tanks.
SUBSTRATE	Newsprint, improved newsprint and other uncoated paper stocks
WASH UP	Hydrocarbon based washes, such as Varn Journal Wash or Varn Web Wash, are recommended.
FOUNTAIN SOLUTIONS	The Varn Media Fount range is recommended. Newsman 683 Black is also suitable for use with most acid, alkali or neutral founts. <i>Contact your Flint Group representative for the most suitable fount for your system.</i>
PLATES	Suitable to be used with all types of negative, positive and CtP plates.
BLANKETS	DayGraphica News Printer range of blankets is recommended. <i>Contact your Flint Group representative for the most suitable blanket for your press.</i>
INK ADJUSTMENT	Newsman 683 black is a press ready ink and requires no adjustment.
HEALTH & SAFETY	Newsman 683 black is classified as non-dangerous goods. For further information refer to the product MSDS.

Flint Group P/L
25-51 Berends Drive,
Dandenong South, Victoria, 3175.

P: +61 3 9797 5400
F: +61 3 9768 2555
www.flintgrp.com

This information is based on our experience and on results obtained in the laboratory, using specific processes and types of application. In view of the diversity of substrates and printing conditions, this data is communicated for information purposes only and is provided without any warranty on our part and must be authenticated by industrial tests before the products are used. Improvements are being made to our products on an ongoing basis and we therefore reserve the right to modify their composition as well as the contents of our technical data sheets. We disclaim any liability for applications for which this ink series is not foreseen.

FlintGroup

