

nylosolv[®] A

Fast and efficient washout solvent for safe processing of photopolymer printing plates

Product features

- Ideal for high quality processing of conventional and digital photopolymer printing plates
- High flashpoint allows washout at higher temperatures
 - faster washout time
 - less plate swelling
 - less drying time
 - improved safety in transit and in storage
- Optimised formulation with a three component mixture of hydrocarbons and alcohol
- Easy distillation under vacuum, with minimal loss of components and convenient component adjustment
- Low odour for comfortable work
- Gentle and environmentally friendly

Safety and technical information*

Optimal washout temperature	35 °C 95 °F
Flashpoint	> 63 °C > 145 °F
Transport and Storage	See material safety date sheet
Ignition temperature	200 °C 392 °F
Density	0.841 g/cm ³ (20 °C 68 °F)
Packing Unit	30 l/can 200 l/barrel 950 l/ibc container

*Please find further information in our nylosolv[®] User Guide.

You are welcome to contact us for further information.

Flint Group Flexographic Products
Sieglestrasse 25
70469 Stuttgart
Germany

T +49 711 9816-541
F +49 711 9816-801
info.flexo@flintgrp.com
www.flintgrp.com

All information in this document is based on our present knowledge and experience at the time of printing. Due to the multitude of factors influencing the processing and application of our products, it does not exempt the user from testing and calibrating. Nor does it imply any legally binding assurance concerning specific properties of the products or the suitability for a particular application. The responsibility of observing any possible industrial property rights, laws and regulations is the obligation of the user. Subject to technical changes without prior notice. Product names marked ® are registered trademarks of Flint Group.

2015-08