



rotec[®] Blue Light Sleeve

Lightweight and durable sleeve for conventional plate mounting with adhesive tape

Available wall thicknesses from 0.080" to 4.0"
Special sizes available on request

Product advantages

- Superior lifetime due to excellent durability
- Optimal stability with low weight
- Suitable for all plate and adhesive tape thicknesses
- Simple adhesive tape dismounting
- Can be combined with various types of adapters
- Easy and reliable handling

Product features

- Hard sleeve for traditional plate mounting with adhesive tapes for nearly all diameters and lengths
- Extremely durable polyurethane surface (75 Shore D) – generally scratch and solvent resistant if handled correctly (see rotec[®] User's Guide)
- Proven rotec[®] interior design of synthetic resin and fiber compound assures long lasting and consistent mounting characteristics
- High-precision grinding (TIR \leq 0.025 mm/0.001") measured on carrier cylinder at TIR \leq 0.005 mm/0.0002"
- Tolerance of face-length according to DIN ISO 2768 T1 c
- Above wall thicknesses available from North America

Please contact your Regional Sales Manager for additional information.

Customer Service
Flint Group Flexographic Products
95 Glenn Bridge Road
Arden, NC 28704

T +1 877 768 3248
F +1 828 681 9595
info.flexo@flintgrp.com
www.flintgrp.com

All information in this document is based on our present knowledge and experience at the time of printing. Due to the multitude of factors influencing the processing and application of our products, it does not exempt the user from testing and calibrating. Nor does it imply any legally binding assurance concerning specific properties of the products or the suitability for a particular application. The responsibility of observing any possible industrial property rights, laws and regulations is the obligation of the user. Subject to technical changes without prior notice. Names marked ® are registered trademarks of Flint Group.