



rotec[®] Hybrid Sleeve

Thin-walled fibreglass composite sleeve with a particularly hard surface for traditional plate mounting

Available wall thickness from 0.9 mm to 2.0 mm
Special sizes available on request

Product advantages

- **Efficient and cost effective**
 - Long service life¹
 - Allows to leave print jobs mounted
 - Available for almost any face length or print repeat
- **Convenient handling**
 - Solvent and ink resistant surface
 - General resistance to cuts and scratches¹
 - Long-lasting and consistent mounting characteristics
 - Easy adhesive tape dismounting
- **Meets high quality standards**
 - Low tolerances due to high precision grinding
 - Excellent dimensional stability even at fluctuating temperatures and high air humidity
 - Manufactured with state-of-the-art technology

¹ if handled correctly (see rotec[®] User's Advice)

rotec® Hybrid Sleeve

Product specifications

| | |
|------------------------------|--|
| Runout tolerance | TIR ≤ 0.025 mm (measured on carrier cylinder at TIR ≤ 0.005 mm) |
| Face-length tolerance | according to DIN ISO 2768 T1 c |
| Wall thicknesses | from 1.0 mm to 2.0 mm special sizes available on request |
| Lengths | standard: up to 2400 mm special sizes: up to 3700 mm |
| Diameters | almost all diameters |
| Repeats | almost all print repeats |
| Material | extremely durable fibreglass composite surface (85 Shore D) proven rotec® interior design of synthetic resin and fibre compound |
| Notch | available with notch and position mark on opposite end |
| Adapters | can be combined with various types of adapters or air cylinders |
| Printing plates | suitable for all plate thicknesses |
| Adhesive tapes | suitable for all tape types and thicknesses |
| Handling | see rotec® User's Advice |

You are welcome to contact us for further information.

Flint Group Flexographic Products
Solmsstraße 83
48683 Ahaus
Germany

T +49 711 9816-541
F +49 711 9816-801
info.flexo@flintgrp.com
www.flintgrp.com

All information in this document is based on our present knowledge and experience at the time of printing. Due to the multitude of factors influencing the processing and application of our products, it does not exempt the user from testing and calibrating. Nor does it imply any legally binding assurance concerning specific properties of the products or the suitability for a particular application. The responsibility of observing any possible industrial property rights, laws and regulations is the obligation of the user. Subject to technical changes without prior notice. Product names marked ® are registered trademarks of Flint Group.