

*Rely on us.*SM

Varn® Media Fount T

High performance, clean label fountain solution

Fountain solution for Coldset turbo dampening systems

Product Features

- Varn® Media Fount T features a revolutionary formulation, providing 'clean label' status with no hazardous classification - giving unrivalled environmental benefits to the newspaper industry.
- Varn® Media Fount T is based on brand new technology and is truly revolutionary, formulated for the next generation of high speed newspaper presses.
- Varn® Media Fount T offers greater stability on press, even at high speeds and temperatures allowing for even faster start-ups whilst minimising waste copy.
- In addition Varn® Media Fount T has been formulated to meet the requirements of the latest CtP technology used in today's newspaper industry.

Advantages of Varn® Media Fount T

- Extremely quick, clean start up.
- Stable pH controlled system.
- Advanced anti-corrosion technology.
- Safe for use with CtP.
- OEM approved.
- Clean label.
- Reduces waste.



FlintGroup

Varn® Media Fount T

Features	Advantages	Benefits
<ul style="list-style-type: none">• Clean label.	<ul style="list-style-type: none">• No hazardous labelling.	<ul style="list-style-type: none">• Safer to the environment and the printer.
<ul style="list-style-type: none">• Optimised low foam formulation.	<ul style="list-style-type: none">• Specifically formulated for turbo dampening systems.	<ul style="list-style-type: none">• Consistent press performance, no need for constant adjustments.
<ul style="list-style-type: none">• Exclusive corrosion package.	<ul style="list-style-type: none">• Ultra low corrosion.	<ul style="list-style-type: none">• Long press life.
<ul style="list-style-type: none">• Unique desensitisers.	<ul style="list-style-type: none">• Extremely fast, clean start-ups.	<ul style="list-style-type: none">• Less waste therefore improved productivity and saleable copy.

Product code	KT10-OMTG-#### (final 4 digits relate to pack size). Also available in a version to suit hard/alkaline waters of more than 250 ppm calcium carbonate and/or 15° dh hardness - KT10-OT2G-####.
Pack sizes	200kg (O1N1) and 1000kg (O1U0).
Recommended dosage	Between 2% and 4% concentration to reach pH 4.5 - 5.5, depending on local water conditions.
Approvals	OEM approved (KBA and manroland Coldset Web presses) in accordance with Fogra corrosion and elastomer swell testing criteria. WIFAG corrosion approval.

More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Print Media Europe
Varn House, Brinell Drive,
Northbank Industrial Park, Irlam,
Greater Manchester, M44 5BL, UK.

T +44 (0)161 775 5412
F +44 (0)161 775 5415
printmedia.eu@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Product names followed by ® are trademarks registered by Flint Group Incorporated.