

Rely on us.<sup>SM</sup>



# Novacoat® 8866 PROTECT overprint sealer

Silk matt overprint sealer for excellent rub protection

K+E® oil-based overprint varnishes for sheetfed offset

## Produkteigenschaften

- Novacoat® 8866 PROTECT is a high viscosity, silk matt, oil-based overprint sealer based on BIO-binders, that offers within a short time period excellent rub protection.
- It is optimally suited for straight-line printing on all multi-colour presses and may be used for perfecting.
- Novacoat® 8866 PROTECT is particularly well suited for wet on wet applications and well suited for wet on dry applications.
- Due to the silk matt setting of Novacoat® 8866 PROTECT, the visible impression of printed sheets is neutral, this facilitates increased resistance to mechanical gloss matt effects.

## Advantages of Novacoat® 8866 PROTECT

- Excellent rub protection.
- Very well suited for straight-line printing and may be used for perfecting.
- Particularly well suited for wet on wet and well suited for wet on dry applications.
- Fastest oxidative drying.
- Ideal for coated and uncoated paper and board.



FlintGroup

# Novacoat® 8866 PROTECT



Printing properties						
Gloss	Matt effect	Wet on Wet suitability	Wet on Dry suitability	Setting	Rub protection	Suitability for Perfecting
-	3	7	5	6	7	4
1 = Characteristic weakly expressed 7 = Characteristic strongly expressed						
<i>The assessment of the varnish properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very thick layers of varnish, the classification of certain properties may be different.</i>						

Novacoat® 8866 PROTECT overprint sealer

#### Drying properties

Oxidative drying.

#### Substrates

Coated and uncoated paper and board.

#### Remarks

Printing inks varnished with an oil-based overprint varnished don't need any specific fastness properties.

Optimal application quantity: 1.5 – 1.8 g/m<sup>2</sup>

If the quantity remains within this range optimal rub protection can be achieved.

#### Exceptions

Don't use Novacoat® 8866 PROTECT on food packaging without functional barrier.

### More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

#### Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

#### You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

Flint Group  
Packaging & Narrow Web  
Sieglestrasse 25  
70469 Stuttgart, Germany

T +49 711 98 16-0  
F +49 711 98 16-700  
sheetfed@flintgrp.com  
www.flintgrp.com

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).