

# Novasens® 225139 PREMIUM

Cold foil glue for gold foils

## Functional ink for sheetfed offset

### Product features

- Novasens® 225139 PREMIUM is a low-odour and low-migration cold foil glue for gold foils, that is used in cold foil applications systems such as manroland InlineFoil, Heidelberg foil star and KBA ColdFoil. In contrast to previous effect foil applications, for which a letterpress or flexographic unit is necessary, these new systems apply the cold foil using two conventional offset printing units.
- Novasens® 225139 PREMIUM is applied through the first inking unit and an offset printing plate as a spot application, or to the entire sheet. The following printing unit is for applying the foil to the parts of the substrates coated with glue. Subsequent overprinting of the foil enables a great variety of colour nuances to be achieved.
- The glue is ready-to-print, can be handled as a conventional offset ink and offers good printability.
- Novasens® 225139 PREMIUM is particularly well suited for the use on coated substrates in straight-line-printing on all multi-colour printing presses equipped with cold foil application systems.

### Advantages of Novasens® 225139 PREMIUM

- Suitable for cold foil application systems.
- Ready-to-print.
- Low-odour, low-migration.
- The glue complies with the requirements for printing inks for food packaging (according to EuPIA Guideline).
- Good printability.
- Ideally suited for coated papers and board.

# Novasens® 225139 PREMIUM

Denomination	Product code	Fastness properties			Printing properties							
		Ethanol	Solvent mixture	Alkali	Gloss	Setting	Oxidative drying	Rub resistance	Rapid further processing	Suitability for gloss coated papers/board	Suitability for uncoated papers/board	Suitability for matt coated papers/board
<b>Novasens® 225139 PREMIUM cold foil glue for gold foils</b>	<b>VI37-12AN-XSBM</b>	+	+	+	1	6	1	1	1	7	2	6
					1 = Characteristic weakly expressed 7 = Characteristic strongly expressed							
<b>Fastness properties according to ISO 2836:</b> + = Resistance provided - = Resistance not provided					<b>The assessment of the colour properties was made under standardised printing conditions. In individual cases, under special conditions, as in printing with very high densities, the classification of certain properties may be different.</b>							

## Drying properties

Drying by absorption.

## Substrates

Ideally suited for coated papers and board.

In view of the wide substrates offered by various manufacturers we strongly recommend carrying out your own tests before starting a print run.

## Additives

Only Flint Group released additives may be used. As thinner we recommend Novasens® PREMIUM Reducer and for tack reduction Novasens® PREMIUM Redux Paste.

## Remarks

Glue can be washed off from rollers with standard washes.

Novaspot® 225139 PREMIUM was tested with standard foils.

Novaspot® 225139 PREMIUM is particularly suited for the production of packaging that complies with the requirements of the EU-regulation 1935/2004 and 2023/2006 as well as with the Swiss Ordinance 817.023.21. Additionally the glue meets the requirements of the EuPIA Guideline "Printing Inks applied to the non-food contact surface of food packaging materials and articles".

## More products. Streamlined access. Greater results.

Flint Group offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

### Inks & Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

### You are welcome to contact us for further information.

The aim of our technical documents is to inform and advise our customers. The information provided herein is correct to the best of Flint Group's knowledge. No liability for any errors, facts or opinions is accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

**Flint Group**  
**Commercial, Publication & Sheetfed Inks**  
 Sieglestrasse 25  
 70469 Stuttgart, Germany

**T +49 711 98 16-0**  
**F +49 711 98 16-700**  
**sheetfed@flintgrp.com**  
**www.flintgrp.com**

Product names followed by ® are trademarks registered by Flint Group (represented by Flint Group US LLC or Flint Group Germany GmbH).